



# Ultra Band Lok

## Safety Data Sheet

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product name : Ultra Band Lok

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : For RX only

#### 1.3. Supplier

##### Manufacturer

Reliance Orthodontic Products Inc. 1540 West Thorndale Ave.  
Itasca, IL 60143 USA  
800-323-4348 / 630-773-4009, during normal business hours  
www.relianceorthodontics.com

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC - 24-Hour Hazmat Emergency Communications Center  
Domestic: 1-800-424-9300 Outside the U.S.: 1-703-527-3887, collect calls accepted

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS-US classification

Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Specific target organ toxicity (single exposure) Category 3	H335	May cause respiratory irritation

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Hazard statements (GHS-US) :

H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation  
H335 - May cause respiratory irritation

Precautionary statements (GHS-US) :

P261 - Avoid breathing vapors  
P264 - Wash hands thoroughly after handling  
P271 - Use only outdoors or in a well-ventilated area  
P272 - Contaminated work clothing must not be allowed out of the workplace  
P280 - Wear eye protection, face protection, protective gloves  
P302+P352 - If on skin: Wash with plenty of Wash skin with soap and water  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P312 - Call Call a doctor, a POISON CENTER if you feel unwell  
P321 - Specific treatment (see First aid measures on this label)  
P332+P313 - If skin irritation occurs: Get medical advice/attention  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P362+P364 - Take off contaminated clothing and wash it before reuse  
P363 - Wash contaminated clothing before reuse  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed  
P405 - Store locked up  
P501 - Dispose in a safe manner in accordance with local/national regulations

#### 2.3. Other hazards which do not result in classification

No additional information available

#### 2.4. Unknown acute toxicity (GHS US)

Not applicable

# Ultra Band Lok

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 3: Composition/Information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
SG-355RG4000CMP3	(CAS-No.) NA	30 - 50	Eye Irrit. 2, H319 STOT SE 3, H335
BisGMA	(CAS-No.) 1565-94-2	10 - 30	Skin Irrit. 2, H315 Eye Irrit. 2B, H320 Skin Sens. 1, H317
Barium Monoxide	(CAS-No.) 1304-28-5	3.9081 - 6.5135	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332
2-Hydroxyethyl Methacrylate	(CAS-No.) 868-77-9	1 - 5	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
3-(Trimethoxysilyl)propyl-2-Methyl-2-Propenoic Acid	(CAS-No.) 2530-85-0	0.26054 - 3.9081	Skin Sens. 1B, H317

Full text of hazard classes and H-statements : see section 16

### SECTION 4: First-aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : Call a poison center/doctor/physician if you feel unwell.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.
- First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

#### 4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after inhalation : May cause respiratory irritation.
- Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.
- Symptoms/effects after eye contact : Eye irritation.

#### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam.

#### 5.2. Specific hazards arising from the chemical

- Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

#### 5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. Avoid breathing mist, vapors. Avoid contact with skin and eyes.

##### 6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Mechanically recover the product.

# Ultra Band Lok

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Use only outdoors or in a well-ventilated area. Avoid breathing mist, vapors. Avoid contact with skin and eyes. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 2-Hydroxyethyl Methacrylate (868-77-9)

Not applicable

#### BisGMA (1565-94-2)

Not applicable

#### Barium Monoxide (1304-28-5)

Not applicable

#### 3-(Trimethoxysilyl)propyl-2-Methyl-2-Propenoic Acid (2530-85-0)

Not applicable

#### SG-355RG4000CMP3 (NA)

Not applicable

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Protective gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Solid

Appearance : Viscous resin paste.

Color : Straw / Deep blue

Odor : Acrylic

Odor threshold : No data available

pH : No data available

Melting point : No data available

# Ultra Band Lok

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: Not applicable
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: Not applicable
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: No data available
Explosion limits	: Not applicable
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

<b>2-Hydroxyethyl Methacrylate (868-77-9)</b>	
LD50 oral rat	5564 mg/kg body weight (Rat; Experimental value)
LD50 dermal rabbit	> 5000 mg/kg body weight (Rabbit; Experimental value)
ATE US (oral)	5564 mg/kg body weight

<b>Barium Monoxide (1304-28-5)</b>	
ATE US (oral)	500 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

<b>3-(Trimethoxysilyl)propyl-2-Methyl-2-Propenoic Acid (2530-85-0)</b>	
LD50 oral rat	> 2000 mg/kg body weight (Rat; Literature study)
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Literature study)

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

# Ultra Band Lok

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: May cause respiratory irritation.
Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

<b>2-Hydroxyethyl Methacrylate (868-77-9)</b>	
LC50 fish 1	227 mg/l (LC50; 96 h)
EC50 Daphnia 1	171 mg/l (NOEC; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
EC50 Daphnia 2	380 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 1	836 mg/l (ErC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)
Threshold limit algae 2	345 mg/l (EbC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)

<b>Barium Monoxide (1304-28-5)</b>	
TLM fish 1	10 - 100 ppm (96 h, Pisces, Literature study)

<b>3-(Trimethoxysilyl)propyl-2-Methyl-2-Propenoic Acid (2530-85-0)</b>	
LC50 fish 1	175 mg/l (LC50; 96 h)
EC50 Daphnia 1	> 100 mg/l (EC50; EU Method C.2; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
LC50 fish 2	> 100 mg/l (LC50; EU Method C.1; 96 h; Brachydanio rerio; Semi-static system; Fresh water; Experimental value)
EC50 Daphnia 2	>= 100 mg/l (NOEC; EU Method C.2; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 1	> 100 mg/l (EC50; EU Method C.3; 72 h; Scenedesmus subspicatus; Static system; Fresh water; Experimental value)
Threshold limit algae 2	> 100 mg/l (EC50; EU Method C.3; 72 h; Scenedesmus subspicatus; Static system; Fresh water; Experimental value)

#### 12.2. Persistence and degradability

<b>2-Hydroxyethyl Methacrylate (868-77-9)</b>	
Persistence and degradability	Readily biodegradable in water. Biodegradability in soil: no data available. Adsorbs into the soil.

<b>Barium Monoxide (1304-28-5)</b>	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable (inorganic)
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

<b>3-(Trimethoxysilyl)propyl-2-Methyl-2-Propenoic Acid (2530-85-0)</b>	
Persistence and degradability	Readily biodegradable in water.

# Ultra Band Lok

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 12.3. Bioaccumulative potential

<b>2-Hydroxyethyl Methacrylate (868-77-9)</b>	
BCF fish 1	1.3 - 1.5 (BCF)
Log Pow	-0.55 - 0.49 (0.42; Experimental value; OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
<b>Barium Monoxide (1304-28-5)</b>	
Bioaccumulative potential	No bioaccumulation data available.
<b>3-(Trimethoxysilyl)propyl-2-Methyl-2-Propenoic Acid (2530-85-0)</b>	
Log Pow	0.75 (Calculated)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

### 12.4. Mobility in soil

<b>Barium Monoxide (1304-28-5)</b>	
Ecology - soil	No (test)data on mobility of the substance available.

### 12.5. Other adverse effects

Effect on the global warming : No known effects from this product.  
GWPmix comment : No known effects from this product.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

Other information : No supplementary information available.

### TDG

### Transport by sea

### Air transport

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

<b>2-Hydroxyethyl Methacrylate (868-77-9)</b>
Listed on the United States TSCA (Toxic Substances Control Act) inventory

### 15.2. International regulations

#### CANADA

No additional information available

#### EU-Regulations

No additional information available

#### National regulations

No additional information available

### 15.3. US State regulations

No additional information available

# Ultra Band Lok

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 16: Other information

Full text of H-phrases:

H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H320	Causes eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation

SDS US (GHS HazCom 2012)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*